

DAIMLER TRUCKS PERTH

SHIRE OF WICKEPIN

SUPPY & DELIVERY OF (1) ONE TRUCK TIPPER

VP206002 RFQ-6

LANCE ANNAN - 0437988451



Shire of Wickepin

Request for:

Supply & Delivery of One (1) Truck Tipper GVM 6,500 KG

VP reference Number: VP206002

Buyer reference Number: RFQ-6

Opens 21/Sep/20 : Closes 30/Oct/20 05:00 PM W. Australia Standard Time

Cut-off date for supplier queries: Friday 30/Oct/20 05:00 PM W. Australia Standard Time

To be eligible for consideration, you must finalize and submit your response online via VendorPanel before the 30/Oct/20 05:00 PM W. Australia Standard Time.

The buyer has attached 1 document to this request. You can find it in this zip file under '/RFXDocs/'

https://www.vendorpanel.com.au

DAIMLER TRUCKS PERTH

OPERATED BY ADTRANS







REF: 20138

28/10/2020

SHIRE OF WICKEPIN The Chief Executive Officer 77 Wogolin Rd Wickepin WA 6370

SUPPLY & DELIVERY OF ONE (1) TRUCK TIPPER

VP206002 RFQ-6

Thank you for the opportunity to provide you with the following quotation for a new FUSO CANTER 815 LWB DCT 'SAFETY PACK' (FEB71GR3FBC) REAR TIP BODY

We are sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Should any further details be required, please do not hesitate to contact the undersigned, on (08) 9311 7400, who will gladly assist.

Yours faithfully DAIMLER TRUCKS PERTH

LANCE ANNAN Fuso Sales Consultant MICHAEL ALLEN
New FUSO Truck Sales Manager

Mailing Address PO Box 1914 Midland DC WA 6936

Mercedes-Benz - are registered trademarks of Daimler AG. Stuttgart. Germany Freightliner is a registered trademark of Freightliner LLC. USA Fuso is a registered trademark of Mitsubishi Fuso Trucks & Bus Corporation, Japan

Daimler Trucks Perth 4 Ulm Place Perth Airport WA 6105 Tel+618 9311 7400 www.daimlertrucksperth.com.au

FUSO CANTER 815 LWB DCT 'SAFETY PACK' (FEB71GR3FBC)

GVM / GCM: GVM 7,500kgs / GCM 11,000kgs (optional 4500 GVM)

ENGINE: Fuso 4P10-T4 Variable Geometry Turbo Diesel (ADR80/03 Euro 5 & EEV)

4cyl DOHC, Air to Air Intercooled, Bosch Common Rail direct injection Diesel Particulate Filter (DPF) exhaust with in dash DPF display status. Colour dash display DPF Status with 0 – 9 (empty-full) Parked regeneration is Possible from 7 – 9 bars. 110 Kw / 150 HP @2840-3500 rpm 370Nm torque @

1350-2840 rpm. Flat torque curve.

FUEL: Bosch common rail injection system, 100 litre fuel tank with lockable fuel cap.

CLUTCH: Dual clutch (wet multi plate) no clutch pedal in automated manual model.

TRANSMISSION: 6 speed overdrive Automated Manual transmission with Auto and Manual modes.

Virtually instant gear changes. In dash gear lever with Park Brake Position.

AXLE FRONT: Reverse Elliot "I" Beam. Capacity 2600kgs.

SUSPENSION FRONT: Multi leaf with stabiliser bar. Double acting shock absorbers.

STEERING: Rack and pinion Power steering with telescopic / tilt adjustable steering column.

AXLE REAR: Full floating banjo type, ratio 4.875:1. Capacity 4500kgs

SUSPENSION REAR: Semi-Elliptic leaf with Double acting shock absorbers.

BRAKES: Hydraulic dual circuit Front and Rear Discs. Twin calliper front and rear.

ABS plus EBD (Electronic brake distribution) Exhaust brake.

Transmission mounted park brake.

Advanced Emergency Braking (AEBS) **ACTIVE SAFETY:**

Lane Departure Warning System (LDWS)

Electronic Stability Program (ESP)

WHEELS & TYRES:

7 x single piece disc rims, 16x5 wheels with 205/85R16 Tyres. 5 stud 208mm PCD. All steel fixed 7 seat Cab with isolated rubber mounting. ECE-R29 Approval. CAB:

Standard Front and Rear Air Conditioning with separate controls. Heater / Demister.

Side doors reinforced with impact beams, laminated windscreen with tinted Side and rear glass. Driver seat suspended with LH armrest and lumbar support.

Intermittent wipers, washers on wiper blades. Dual Airbags & Seat Belt

Pre-Tensioners to driver and LHS passenger only. Electric Windows, front only, Keyless central locking, 12V accessory outlet. External heated convex mirrors,

Reverse beeper, 2 x cup holders. Removable engine access panel. Colour Information

Display for fuel consumption, water temp, DPF bar chart & Tripmeters.

Reinforced Tapered Channel low tare weight chassis. 750mm width. 440 MPA. CHASSIS:

Wheelbase 3400mm.

7" LCD with touchscreen control, Bluetooth hands free phone calls, Bluetooth music streaming **MULTIMEDIA:**

compatible, AM/FM Radio, Digital Radio, USB & 3.5mm Aux port and reverse camera compatible

(1 camera included). Sat Navigation with Heavy Vehicle weight, length, height & haz mat

selectable restrictions with 3yr free map updates.

Voltage 12V negative earth. Alternator 110 amp. 2 x 12 volt 70 Ah / 5hr batteries. **ELECTRICAL:**

Halogen 55W / 60W Headlamps.

12 month OR 30,000km Service intervals. SERVICING:

OPTIONS:

Basic/Powertrain - 5 Years OR 200,000km. WARRANTY:

Cab Perforation/Anti Corrosion - 5 Years Rear mounted parking sensor kit (hi or low)

USB quick charge kit

Qi wireless charging pocket for mobile devices

Tyre pressure monitoring system

FUSO CANTER 815 LWB DCT 'SAFETY PACK' (FEB71GR3FBC) REAR TIP BODY

PRICE:	List Price Less Allowance	<u>\$</u> -\$	61,968.00 19,174.02
	2020 Plated Cab Chassis Only	\$	42,793.98
FIT OUT:	 Body Builders Quote 10714 Attached Additional 100Ltr Fuel Tank PTO Activation Stone Guard Sun visor Window Tint UHF Radio Canvas Seat Covers HD Rubber Floor Mats Work Shop/Chassis/Electrical Manuals First 5,000km Service Covered by Fuso Reverse Camera as Standard Delivery to Shire of Wickepin 		
	Total:	\$	29,745.00
	 5 year factory warranty 200,000km Non factory items including truck body's come w A 12 month warranty 3 years map updates on sat-nav. 7" LCD touchsc Bluetooth 		included included included
PRICE	Sub Total	\$	72,538.98
	PLUS 10% GST Sub Total Including GST	\$ <u>\$</u>	7,253.90 79,792.88
LICENSING:	Licence Fees to June 30 th 2020	\$	200.00
	TOTAL INVESTMENT	\$	79,992.88
TRADE-IN:	2015 Hino Tipper – WK 698	-\$	35,000.00
	CHANGE OVER	AUTO\$ MANUAL\$	44,992.88 42,929.12

This trade-in is my own unencumbered property except as otherwise stated above, and has not been subject to flood Conditions, hail damage, repaired due to hail damage, is not on the Write-off Register, or excluded from Manufacturers Warranty and has not been used as a taxi or hire car. The vehicle is not subject to any defect or traffic infringement notice and The kilometres on the odometer are true and accurate

SERVICE: 30,000km or 40,000km / 12 month Service intervals.

SERVICE PLANS 4 levels of cover, ask Daimler Trucks Perth for more details.

CANTER and ROSA WARRANTY

Canter / Rosa standard Warranty – 5 Years, 200,000 km or 4000 operating

hours (whichever comes first).

FIGHTER WARRANTY FK Models standard Warranty – 5 Years, 300,000 km or 6000 operating hours

(whichever comes first).

1627 & 2427 Fighter standard Warranty - 5 Years, 350,000 km or 7000

operating hours (whichever comes first).

HEAVY WARRANTY 5 Years, 500,000kms or 10,000 operating hours (whichever comes first)

24HR ROADSIDE ASSIST National roadside assist covers Fuso clients for the life of their vehicle from

delivery. (Conditions apply) Daimler Trucks Perth for more details

PLEASE NOTE Please note all accessories fitted are not covered by the vehicle manufacturer's

warranty. All accessory warranties are subject to warranty provided by the

supplier.

MAIN WORKSHOP Daimler Trucks Perth Service Centre operates from 8am to Midnight Monday

through Friday and Saturday morning where prior arrangements have been

made.

PLEASE NOTE Specifications are subject to change without notice.

PRICING Subject to those ruling at time of delivery.

PAYMENT Possession of your new vehicle can only be passed on to you after full

settlement of all outstanding funds including licensing charges and any other

accessories ordered.

FINANCE COVER: AGILITY Allow's us to guarantee the future value of your vehicle

FAST TRACK APPROVAL Minimal paperwork required.

COMPETITIVE RATES With flexible payment options.

OPERATING LEASE Choose your annual kilometres & include scheduled servicing.

INSURANCE Insure your asset with policies developed specifically for your Fuso.

LOAN PROTECTION Protect your repayments should something happen to you.

20138 - Quote

22,570.00

22,570.00

x 1

Daimler Trucks Perth - Rear Tip Body - RFQ-6 Shire of Wickepin

QUOTE 10714

Vehicle Details - TBA

Rear Tip Body

2.1 General Specifications

The machine shall comply with the following specifications.

- 5. End tip operated form cab of tuck
- 6 Hydraulic Hoist Ram capable to lift 10 ton
- 7 Tool Box to fitted between cab and tipper 2400mm L x 500mm W $\scriptstyle\rm X$ 500mm H Lid type door hinged on the rear side box lid opening pass 110 degrees so it sits open against tipper body
- 8 Rear tailgate be able to swing and to be able pined to the side and removable. In rear tipper mode tailgate is have a release system by air ram operated form cab of tuck
- 9. Tipping body 3600 mm long by 2400 mm wide with drop sides at 450mm in depth and tie rail under the body
- 10 The height of tray floor from ground to be 1m
- 11. Tow point 50 mm ball
- 12. Seven pin plug round small
- 14 Master switch electrical disconnect and emergency stop.
- 21 Flashing beacon LED and to meet work safe standards x 2 to be fitted left and right side of roof of cab.

September 22, 2020

VALID UNTIL

December 8, 2020 at 12:48PM

FOR

Daimler Trucks Perth*

Lance Annan

EMAIL

lannan@daimlertrucksperth.c om.au

FROM

Gary Nicholls

PTE Group Pty Ltd

99 Dowd Street

WELSHPOOL WA 6106


Licensed Repairer: MRB3891

www.ptegroup.com.au

PHONE

08 9356 1192

16 139 227 071



19 Reversing alarm and camera to be fitted. Factory PTO switch



Subtotal **GST 10%**

Total AUD including GST

22,570.00 2,257.00

\$24,827.00

Account Information

COD account unless approved for a 30 day EOM account.



SAFEST CANTER EVER SAFETY FEATURES AS STANDARD

ADVANCED EMERGENCY BRAKING

ANTI –SLIP REGULATOR

LANE DEPARTURE WARNING

ELECTRONIC STABILITY PROGRAM

ABS PLUS ELECTRONIC BRAKE FORCE DISTRIBUTION

WARRANTY

5 YEARS WARRANTY UP TO 200,000KM

SERVICING INTERVALS 30,000KM



CANTER 815

4X2 / WIDE CAB / MANUAL OR DUONIC DCT



OUR SAFEST CANTER EVER WITH AEBS, LDWS AND ESP STANDARD CLASS LEADING TARE WEIGHT AND 30,000KM SERVICE INTERVALS.

Power/Torque 7,500kg 11,000 kg 110 KW / 370 NM

- Light rigid licence required.
- Can be derated and driven with a passenger car licence.

SPECIFICATIONS

FUSO

MODEL

- 4x2 815 Wide Cab MWB 6 Sp. Duonic AMT (FEC71ER3SFBC) 4x2 815 Wide Cab LWB 6 Sp. Duonic AMT (FEB71GR3SFBC) 4x2 815 Wide Cab MWB 5 Sp. MAN (FEC71ER4SFBC) 4x2 815 Wide Cab LWB 5 Sp. MAN (FEB71GR4SFBC)


WHEEL BASE

7,500kg (4,495kg) 7,500kg (4,495kg) 7,500kg (4,495kg) 7,500kg (4,495kg) 3400mm 3850mm 3400mm 3850mm

GVM (optional) GCM (optional)

11,000kg (7,995kg) 11,000kg (7,995kg) 11,000kg (7,995kg) 11,000kg (7,995kg)

Engine	第一条,14条,14条,14条,14条,14条 。
Engine Version	FUSO 4P10-T4 Diesel
Configuration	4 Cyl. In-line DOHC, 4-Valve
Туре	Variable Geometry Turbo Charged Air to Air Intercooled
Displacement	3 litre (2998cc)
Bore	95.8mm
Stroke	104mm
Power (DIN)	110kW @ 2840~3500 rpm
Torque (DIN)	370Nm @ 1350~2840 rpm
Maximum Engine Speed	4100 rpm
Compression Ratio	17.5:1
Cooling System / Oil Cooler	Water cooled,13.7L capacity/ Plate type engine oil cooler
Air Cleaner	Paper Element Type with Restrictor Indicator. Vertical Intake Mounted on Clean Air Side (RH)
Emission Control	Diesel Particulate Filter (DPF) Exhaust Dash Display DPF Status 0~9 (Empty~Full) Parked Regeneration possible from 7~9
Emission Level	ADR 80/03 & EEV rated (Enhanced Environmentally- Friendly Vehicle) Euro 5



Fuel	
Injection System	Bosch Common Rail Direct Injection Bosch Piezo Technology Injectors
Tank Type	Rectangular Steel Tank with Locking Cap
Fuel Capacity *	100 Litres
Filtration	Filter with Water Separator and Indicator Sensor
Notes	*Max Fill to approx 95% of Air Capacity

Cooling	
Fan Drive	Thermo modulated continuous control (Viscous)
Radiator	Corrugated Fin with Expansion Tank

Electrical		
Voltage	12V Negative Earth	
Alternator Capacity	12V-110 amp	
Starter Capacity	12V-2.0kW	
Battery Capacity	2x12V, 70Ah/5hr	
Battery Specification	115D31LX2	
Headlamp Type	Halogen	
Headlamp Capacity	2x55W/60W	

Ciotti		
Clutch Model	A B Fully Automated Dual Clutch (no clutch peda	
Туре	A B Dual Clutch (Wet Multi- plate)	C D Single Dry Plate, Direct Hydraulic Type
Transmission		
Version	Λ Β	CD

Transmission		
Version	A B FUSO Duonic M038S6	C D FUSO M038S5
Type/Speeds	A B 6 Speed Dual Clutch with Auto and Manual Modes	C D 5 Speed with In-Dash Gearshift Lever
Features	A B Virtually Instant Gear Changes In-Dash Gear Lever with Park Brake Position ECO Mode to Minimise Fuel Usage	C D Synchromesh 2nd-5th
Ratios	A B 1st: 5.397 2nd: 3.788 3rd: 2.310 4th: 1.474 5th: 1.000 6th: 0.701 Rev. 5.397	C D 1st: 5.494 2nd: 3.193 3rd: 1.689 4th: 1.000 5th: 0.723 Rev. 4.494
PTO Opening	LH Side	

Front Axle	
Axle Version	FUSO F350T
Туре	Reverse Elliot 'I' Beam
Capacity *	3100kg
Notes	*See MAX LOADING for vehicle capacity.

Front Suspension		
Туре	Multi-Leaf with Stabiliser Bar and Double Acting Shock Absorbers	
Size	1150x70mm Leaves	

Rear Axle			
Туре	Full Floating Ba	пјо Туре	
Axle Version	FUSO R035T		
Capacity*	6000kg		
Ratio	AB	CD	
	5.714:1	5.285:1	
Notes	*See MAX LOA	OING for vehicle capacity.	

Rear Suspension	
Туре	Steel Suspension
Details	Semi-Elliptic Leaf with Stabiliser Bar and Double Acting Shock Absorbers
Size Main Leaves	1250x70mm
Size Helper Leaves	880x70mm
Max Loading	
Front	3100kg
Rear	6000kg
Total	7500kg

Options	
Options	H31: 4495/7995kg GVM/GCM Rating

SPECIFICATIONS

FUSO

MODEL

- 4x2 815 Wide Cab MWB 6 Sp. Duonic AMT (FEC71ER3SFBC) 4x2 815 Wide Cab LWB 6 Sp. Duonic AMT (FEB71GR3SFBC) 4x2 815 Wide Cab MWB 5 Sp. MAN (FEC71ER4SFBC) 4x2 815 Wide Cab LWB 5 Sp. MAN (FEB71GR4SFBC)

WHEEL BASE

3850mm

GVM (optional) 3400mm 3850mm 3400mm

7,500kg (4,495kg) 7,500kg (4,495kg) 7,500kg (4,495kg) 7,500kg (4,495kg)

GCM (optional)

- 11,000kg (7,995kg) 11,000kg (7,995kg) 11,000kg (7,995kg) 11,000kg (7,995kg)

Steering	
Туре	Integral Ball and Nut Type
Steering Column	Tilt/Telescopic Adjustable
Power Assist	Standard

Brakes Hydraulic Dual Circuit with Front and Rear Discs Twin Calliper Front and Rear Туре Size Front ВС

A 235x40mm 252x40mm 310x40mm A B C 252x40mm Size Rear 310x40mm ABS plus EBD (Electronic Brake Distribution) Active Emergency Braking System (AEBS) Electronic Stability Program (ESP) Features

Exhaust Brake

Brake Priority System
Electronic Brake Wear Sensors (From Aug 20 build)

Park Brake Transmission Mounted

Wheels & Tyres

Wheel Type	7 x Single Piece Disc Rims (Including Spare)
Wheel Size	17.5x6.0-127
Wheel Stud Pattern	6 Stud 222.25 PCD
Tyre Size All	215/75R17.5 124/123
Spare Tyre Carrier	Provided

Chassis

Туре	Reinforced Tapered Channel		
Size	A C 212x65x6mm	B D 192x60x6mm	
Width	A C 850mm	B D 752mm	
Tensile Strength	A C 540 MPa	B D 440 MPa	

Instruments	

Gauges	Speedometer with Odometer Tachometer Fuel Level Water Temperature	į.
Colour Information Display	Fuel Consumption DPF Bar Chart from 1~9 Water Temperature Lane Departure Warning Maintenance Reminder System Tripmeters	

Multi-Media Package

Satellite Navigation	Maps with heavy vehicle weight, length, height &
Gatolino Manganen	hazardous material selectable restrictions with 3 years of Map updates
Colour Display	7 inch LCD with touch screen control
Phone Connectivity	Bluetooth® hands free
Audio Visual Entertainment	Bluetooth® music streaming compatible Digital radio DAB+ (also AM/FM for areas not covered by DAB+) USB & 3.5mm/AUX port
Reversing Camera Compatible	Display can accept up to 5 cameras#
Optional Accessories (available at additional cost)	Rear Mounted Parking Sensor Kit (High or Low) USB Quick Charge Kit
	Qi Wireless Charging Pocket for Mobile Devices Tyre Pressure Monitoring System
Notes	# Cameras available through spare parts

Standard Features	1000年的中国中国企业工作,1000年1000年1000年1000年100日			
Airbag(s)	Dual Air Bags and Seat Belt Pre-Tensioners (Driver & Far Side Passenger)			
Active Safety Features	ABS plus Electronic Brake force Distribution (EBD) Advanced Emergency Braking (AEBS) Anti-Slip Regulator (ASR) Electronic Stability Program (ESP) Lane Departure Warning System (LDWS)			
Cruise Control	A B C D Yes No			
Hill Start System	Yes			
Cab Cooling & Heating	Air Conditioner / Heater / Demister			
Accessory Power	12V Accessory Power Outlet / Cigar Lighter			
Driving	Fuso Multimedia Unit Keyless Central Locking Electric Windows Cup Holders (2)			
Storage	Dual Overhead Storage Pockets In-Dash Centre Document Storage Door Storage Pockets Dash Storage Tray (1 DIN) Coat Hooks			
Cab: External	Front End-Outline Marker Lamps Door Side Impact Beams			
Chassis	Reverse Warning Buzzer Factory Reverse Camera with Infrared Display and Audible Pickup (Supply only in Cabin with Cab Chassis)			

Cab Features	多数等4.7%。25克米·0.7%。26克米·0.7%。26米			
Туре	All Steel Forward Control Manual Tilt			
Cab Structure	ECE-R29 European Cab Strength Approved			
Mounting	Hydroelastic 4 Point			
Additional Engine Access	AB CD			
	Removable Engine N/A Access Panel			
Colour	Natural White			
Windscreen Wipers	2 Speed + Intermittent Cycle with Integrated Washer Nozzles			
Rear Vision Mirrors	1 x Internal 2 x External Convex (ECE 46) - Heated			
Seating Capacity	3			
Seat Belts	Lap Sash Belts for Outside Seating Positions Lap Belt for Centre Seat Driver Seat Belt Warning (From Aug 20 build)			
Seat (driver)	Suspended with Weight Adjustment, LH Arm Rest and Lumbar Support			
Seats (passenger)	Flat Folding, 2 Passenger Bench			

Service Interv	ols
Interval*	30,000km or 12 Months (whichever occurs first)
Notes	 based on normal operating conditions and may be reduced when operating under severe conditions.

Warranty				
Basic/Powertrain	5 Years or 200,000kms (whichever occurs first)			
Cab Perforation/Anti Corrosion	5 Years			

Performance			
Turning Circle (kerb to kerb	AC	B D	
- metres)	12.2	13.6	
Road Speed (km/h) at Max	AB	CD	
Engine Speed	127	130	
Engine Speed (rpm) at	AB	CD	
100km/hr (top gear)	2817	2687	
Gradeability at Rated GVM	AB	CD	
(theoretical)*	31%	29%	
Notes	*This is theoretical performance only. Actual performance may vary under different conditions		

SPECIFICATIONS

WFF

MODEL

- 4x2 815 Wide Cab MWB 6 Sp. Duonic AMT (FEC71ER3SFBC)
- 4x2 815 Wide Cab LWB 6 Sp. Duonic AMT (FEB71GR3SFBC) 4x2 815 Wide Cab MWB 5 Sp. MAN (FEC71ER4SFBC) 4x2 815 Wide Cab LWB 5 Sp. MAN (FEB71GR4SFBC)

WHEEL BASE

3400mm 3850mm 3400mm 3850mm

GVM (optional)

7,500kg (4,495kg) 7,500kg (4,495kg) 7,500kg (4,495kg) 7,500kg (4,495kg)

GCM (optional)

11,000kg (7,995kg) 11,000kg (7,995kg) 11,000kg (7,995kg) 11,000kg (7,995kg)

WRA

Mass (estima	ted)*			
Front*	A 1585kg	B 1605kg	C 1565kg	D 1590kg
Rear*	A C 795kg	B 790kg		785kg
Total*	A 2380kg	B 2395kg	C 2360kg	D 2375kg
Notes	wheel, too	* Mass (est.) includes oil and water but excludes spar wheel, tools & fuel. Weights provided are subject to 3.5% variation (+/-)		

Dimensions (mm)				
WFF (Width Front Fender) (mm)	1995			
WRA (Width Rear Axle) (mm)	A C 2144		B D 2034	
WRT (Width Rear Track) (mm)	A C 1670	•	B D 1560	
Width Frame (mm)	A C 850		B D 752	
A - Length Overall (mm)	A C 5935		B D 6685	
C - Front Overhang (mm)	1140			
D - Wheelbase (mm)	A C 3400		B D 3850	
G - Front Axle to Rear of Cab (mm)	525			
H - Rear of Cab to Rearmos Item Behind Cab (mm)	t A B 50		C D 81	
I - Rearmost Item Behind Cab to Rear Axle (mm)	A 2825	B 3275	C 2794	D 3244
J - Frame, Rear Axle to End (mm)	A C 1395		B D 1695	
P - Height Cab to Ground (mm)	A C 2190		B D 2180	
Q - Height Cab to Frame (mm)	A C 1505		B D 1514	
R - Height Rear Frame to Ground (mm)	A C 807		B D 797	

Body Builder's Notes

Notes

Chassis reinforcement must be utilised for Tipper/Demountable type body configurations.
To conform with ADR 13/00 and 14/02 (lighting/mirror requirements) the following must be adhered to at body installation.

- If overall width exceeds 2.1 metres and other than flat type or tipper body is fitted, rear end-outline markers must be installed.
- If overall length exceeds 6.0 metres, side reflectors must be installed.
- If overall length exceeds 7.5 metres and width exceeds 2.1 metres, side marker lamps must be installed
- If overall width is less than 2.2 metres, the mirrors must be modified to project not more than 230mm. To conform with ADR 42/04 (General Safety), rear wheel guards must be fitted to the vehicle.



Call 1800 033 557

or visit fuso.com.au

Unless specified in writing herein the accessories, applications, bodies or equipment depicted in this document are for illustration purposes only and may not be available from Daimler Truck and Bus Australia Pacific Pty Ltd. (ABN 86 618 413 282) (DTB). No representation or warranty whatsoever is given in relation to any accessories, applications, bodies or equipment or suitability of same that are shown herein that may be manufactured, supplied or fitted by a party other than DTB. DTB reserves the right without notice or obligation to discontinue or make changes to the colour, designs, materials and specifications of the products and options referred to herein at any time. For the most current information and in order to ascertain which accessories, applications, bodies and equipment are available from DTB please contact your authorised FUSO Truck and Bus dealer. Fuso is a registered trademark of Daimler Truck and Bus Australia Pacific Pty Ltd. Copyright DTB. Reproduction in whole or part prohibited without written approval. Part Number TSC161B-SSV1. Valid from 27-Aug-20.